Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S1	323	(271/315,187).CCLS.	US-PGPUB; USPAT	OR	OFF	2005/02/01 09:38
S2	129	(271/315,187).CCLS.	EPO; JPO	OR	OFF	2005/02/01 10:11
S3	0	(("SEARCHof:APPLICANT(S)NAME(S).:") or ("(Uwenear4Goldbeck).in. (near4).in.(near4).in. (near4).in. (near4).in. (xxxnear4yyyy).in.(zzzzzzzz).as. Then"or"together. "and"fieldofSearch.Brouse.Tag.1.")). PN.	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/01 10:33
S4	0	(("SEARCHof:APPLICANT(S)NAME(S).:") or ("(Uwenear4Goldbeck).in.")).PN.	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/01 10:34
S5	11	"SEARCHof:APPLICANT(S)NAME(S). :" (Uwe near4 Goldbeck).in.	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/01 10:37
S6	694	"SEARCH of: ASSIGNEE(S) NAME(S).:" (NEXPRESS near4 SOLUTIONS).as.	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 16:40
S7	239	"271"/\$.ccls. and (bushing or sleeve) same drive near3 shaft same cam	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 16:55
S8	165	"271"/\$.ccls. and cam same mount\$5 near "5" bushing same hollow near3 drive near3 shaft same cam and reduce near3 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 16:58
S9	163	"271"/\$.ccls. and cam same mount\$5 near "5" bushing same hollow near3 drive near3 shaft same cam same reduce near3 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:14
S10	0	"271"/\$.ccls. and bushing near3 between near3 cam near3 hollow near3 drive near2 shaft and reduce near3 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:17
S11	0	"271"/\$.ccls. and (bushing or sleeve)near3 between near3 cam near3 hollow near3 drive near2 shaft and reduce near3 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:17
S12	0	bushing near3 between near3 cam near3 hollow near3 drive near2 shaft and reduce near3 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:18

S13	0	(bushing or sleeve) near3 between near3 cam near3 hollow near3 drive near2 shaft and reduce near3 friction	US-PGPUB; USPAT; USOCR;	OR	OFF	2005/02/02 17:18
S14	0	(bushing or sleeve) near3 cam near3 hollow near3 drive near2 shaft and reduce near3 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:19
S15	0	bushing near3 located near3 between near3 cam near3 drive near2 shaft and reduce near3 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:19
S16	0	"271"/\$.ccls. and bushing near3 between near3 cam near3 drive near2 shaft and reduce near3 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:20
S17	0	"271"/\$.ccls. and bushing near3 cam near3 drive near2 shaft and reduce near3 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:20
S18	0	"271"/\$.ccls. and bushing near3 drive near2 shaft and reduce near3 friction and cam	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:21
S19	0	"271"/\$.ccls. and bushing same cam same drive near2 shaft and (reduce near3 friction)	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:21
S20	7	"271"/\$.ccls. and bushing and cam and hollow near5 drive near5 shaft	US-PGPUB; USPAT; USOCR; EPO; JPO	OR ·	OFF	2005/02/02 17:42
S21	19820	"271"/\$.ccls. and bushing near3 between cam near5 drive near5 shaft	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:43
S22	0	"271"/\$.ccls. and bushing near3 between near3 cam near5 drive near5 shaft	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:43
S23	0	"271"/\$.ccls. and bushing same between near3 cam near5 drive near2 shaft	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:44
S24	0	"271"/\$.ccls. and bushing near3 on near5 drive near2 shaft and reduce near5 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:44

S25	0	"101"/\$.ccls. and bushing near3 on near5 drive near2 shaft and reduce near5 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:45
S26	0	"271"/\$.ccls. and bushing near3 on near5 shaft and reduce near5 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 17:46
S27	16	"271"/\$.ccls. and bushing near5 shaft and reduce near5 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 18:00
S28	11	"101"/\$.ccls. and bushing near5 shaft and reduce near5 friction	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2005/02/02 18:00